

Notified Body 1880 - Regulation (EU) No 305/2011

Assessment of Performance Report n.1880-CPR-080-002-23

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this Assessment of Performance Report applies to the construction products

CORTINA CORTINA PLUS

roomheater burning solid fuel without hot water supply

placed on the market under the name or trademark of

AMBIENTE & CALORE S.R.L. VIA GALILEO GALILEI 11 31010 MARENO DI PIAVE (TV) ITALY

This Assessment of Performance Report attests that the performance of the above-mentioned construction product has been assessed in accordance with the harmonized standard

EN 13240:2001/A2:2004/AC:2007

under AVCP system 3 with regard to the essential characteristics listed in Annex 1.

This Assessment of Performance Report will remain applicable as long as neither the harmonized standard, the construction product, nor the AVCP methods are modified significantly.

February 13, 2024

Head of laboratory dr.ssa Claudia Marcuzzi



Notified Body 1880 - Regulation (EU) No 305/2011

ANNEX 1

Essential characteristic	Performance	Basis for the assessment of performance
Reaction to fire	A1	declared by the manufacturer
Distance to combustible materials (minimum distance in mm)	Rear = 60 Sides = 35 Floor = 0	
Risk of burning fuel falling out	Pass	
Emission of combustion products [ref. at 13% O ₂]:	at nominal heat output: CO [1069 mg/Nm ³] CO [0,086 %] NOx [84 mg/Nm ³] OGC [25 mg/Nm ³] Particulate matter [7 mg/Nm ³] at reduced heat output: CO [3367 mg/Nm ³] CO [0,269 %] NOx [67 mg/Nm ³] OGC [319 mg/Nm ³] Particulate matter [15 mg/Nm ³]	Test report n. 1880-CPR-080-001-23
Surface temperature	Pass	
Electrical safety	Pass	declared by the manufacturer
Cleanability Thermal output: Heat output	Pass [10,3 kW] at nominal heat output [4,6 kW] at reduced heat output	Test report n. 1880-CPR-080-23
Efficiency	η [85,3%] nominal heat output η [79,8%] at reduced heat output:	
Flue gas temperature	T[241 °C] nominal heat output T[204 °C] at reduced heat output	declared by the manufacturer